

Printing date 18.01.2006

Reviewed on 18. 01. 2006

1 Identification of substance:

- · Product details:
- · Trade name: Spezialstempelfarbe 191, schwarz
- · Article number: 191
- · Application of the substance / the preparation stamp ink
- · Informing department:

Environment Protection Department

Noris-Color GmbH Ziegelhüttener Straße 1 95326 Kulmbach/Germany

Tel. +49 (0) 9221 92000 Fax. +49 (0) 9221 920090

· Emergency information: s.o.

2 Composition/Data on components:

- · Chemical characterization
- · Description: Mixture of the substances listed below with harmless additions.

· Dangerous components:			
CAS: 34590-94-8 EINECS: 252-104-2	(2-methoxymethylethoxy)propanol		50-100%
CAS: 107-98-2 EINECS: 203-539-1	1-methoxypropan-2-ol	R 10	10-25%
CAS: 71-36-3 EINECS: 200-751-6	butan-1-ol	Xn; R 10-22-37/38-41-67	2.5-10%

· Additional information For the wording of the listed risk phrases refer to section 16.

3 Hazards identification

· Hazard designation:



Xi Irritant

· Information pertaining to particular dangers for man and environment

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

R 10 Flammable.

R 36 Irritating to eyes.

· Classification system

The classification is in line with current EC lists. It is expanded, however, by information from technical literature and by information furnished by supplier companies.

4 First aid measures

- · After inhalation Supply fresh air; consult doctor in case of symptoms.
- · After skin contact The product is not skin irritating.
- · After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

· After swallowing In case of persistent symptoms consult doctor.

C



Printing date 18.01.2006 Reviewed on 18. 01. 2006

Trade name: Spezialstempelfarbe 191, schwarz

(Contd. of page 1)

5 Fire fighting measures

· Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

- · For safety reasons unsuitable extinguishing agents Water with a full water jet.
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.
- · Measures for environmental protection:

Do not allow product to reach sewage system or water bodies.

Inform respective authorities in case product reaches water or sewage system.

Do not allow to enter drainage system, surface or ground water.

· Measures for cleaning/collecting:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

7 Handling and storage

- · Handling
- · Information for safe handling: Open and handle container with care.
- · Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Storage
- Requirements to be met by storerooms and containers: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.

8 Exposure controls and personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Components with limit values that require monitoring at the workplace:

34590-94-8 (2-methoxymethylethoxy)propanol

WEL Long-term value: 308 mg/m³, 50 ppm

107-98-2 1-methoxypropan-2-ol

WEL Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm

71-36-3 butan-1-ol

WEL Short-term value: 154 mg/m³, 50 ppm

- · Additional information: The lists that were valid during the compilation were used as basis.
- · Personal protective equipment
- · General protective and hygienic measures

Keep away from foodstuffs, beverages and food.

Take off immediately all contaminated clothing

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment: Not required.

(Contd. on page 3)



Printing date 18.01.2006 Reviewed on 18. 01. 2006

Trade name: Spezialstempelfarbe 191, schwarz

(Contd. of page 2)

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Tightly sealed safety glasses.

9 Physical and chemical pr	roperties:	
· General Information		
Form:	Fluid	
Colour:	According to product specification	
Odour:	Characteristic	
· Change in condition		
Melting point/Melting range		
Boiling point/Boiling range	: 116°C	
· Flash point:	35°C	
· Ignition temperature:	270.0°C	
· Self-inflammability:	Product is not selfigniting.	
· Danger of explosion:	Product is not explosive. However, formation of explosive air/stea mixtures is possible.	
· Critical values for explosion:		
Lower:	1.1 Vol %	
Upper:	14.0 Vol %	
· Vapour pressure at 20°C:	12.0 hPa	
· Density	Not determined	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix	
· Solvent content:		
Organic solvents:	75.0 %	
Water:	0.0 %	
· Solids content:	24.0 %	

- GB



Printing date 18.01.2006 Reviewed on 18. 01. 2006

Trade name: Spezialstempelfarbe 191, schwarz

(Contd. of page 3)

10 Stability and reactivity

· Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Dangerous reactions No dangerous reactions known
- · Dangerous products of decomposition: No dangerous decomposition products known

11 Toxicological information

- · Acute toxicity:
- Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: Irritant effect.
- · Sensitization: No sensitizing effect known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:

Irritant

12 Ecological information:

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water. Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

13 Disposal considerations

- · Product:
- · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Waste disposal key number: 080111
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· Land transport ADR/RID (cross-border)



· ADR/RID-GGVS/E Class: 3 Flammable liquids.

Kemler Number: 30
UN-Number: 1263
Packaging group: III
Label 3

(Contd. on page 5)



Reviewed on 18. 01. 2006 Printing date 18.01.2006

Trade name: Spezialstempelfarbe 191, schwarz

(Contd. of page 4)

· Designation of goods: 1263 PAINT (not viscous)

· Maritime transport IMDG:



· IMDG Class:

· UN Number:

1263

· Label

3

· Packaging group:

· EMS Number:

IIIF-E,S-E

· Marine pollutant:

No

· Correct technical name: PAINT

· Air transport ICAO-TI and IATA-DGR:



· ICAO/IATA Class:

· UN/ID Number:

1263

· Label

III

· Packaging group: · Correct technical name: PAINT

15 Regulatory information

· Designation according to EC guidelines:

The product has been classified and labelled in accordance with EC Directives / Ordinance on Hazardous Materials (GefStoffV)

- · Code letter and hazard designation of product: Xi Irritant
- · Risk phrases:
- 10 Flammable.
- Irritating to eyes.
- · Safety phrases:
 - Keep out of the reach of children.
- 13 Keep away from food, drink and animal feedingstuffs.
- 25 Avoid contact with eyes.
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
- If swallowed, seek medical advice immediately and show this container or label.
- · National regulations
- · Technical instructions (air):

Class	Share in %
NK	75.0

(Contd. on page 6)





Printing date 18.01.2006 Reviewed on 18. 01. 2006

Trade name: Spezialstempelfarbe 191, schwarz

(Contd. of page 5)

· Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

16 Other information:

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Relevant R-phrases
- 10 Flammable.
- 22 Harmful if swallowed.
- 37/38 Irritating to respiratory system and skin.
- 41 Risk of serious damage to eyes.
- 67 Vapours may cause drowsiness and dizziness.
- · Department issuing data specification sheet: Environment protection department.
- · Contact:

GB